

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5

**DIGITAL PREEMPHASIZER FOR TRANSMISSION OF PCM CODES**

10

**BACKGROUND OF THE INVENTION**

15

Field of the Invention

20

The present invention, disclosed hereinafter, concerns generally an apparatus and method for reducing signal errors attendant to pulse or digital communications transmitted along lossy, band-limited, time-invariant, fixed length, single channel transmission path. In particular, the present invention provides apparatus and method for reducing the error-rate of digital PCM (pulse code modulation) data by means of preemphasis precoding or encoding of the binary PCM data signal prior to transmission on a single channel of a cable system.

25

Description of the Related Art

30

The electronic transmission of data and information by means of pulse and digital systems typically involves either a variable path, such as a radio link between a cellular or cordless is telephone and a repeater node, or alternatively, a fixed, time variant path, such as a copper or fiber optic cable connecting a

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 cable television subscriber's receiver to a provider's  
distribution transmitter.

10 The present invention concerns the latter fixed path. For fixed  
path cable transmissions, the fidelity, i.e. veracity, of the  
transmitted data or information is limited by the bandwidth  
characteristics (also called transfer characteristics, impulse  
response) of the equivalent, passive network representing each  
channel of the transmission line. In many cases, a  
transmission line for pulse and digital communications can  
15 feature multiple channels, permitting separate clocking and error  
correction channels for each data channel; however, in some  
cases, exigent economic and physical demands prescribe a minimal  
size, single channel cable or path for each data or information  
stream. These constraints foreclose the option of a separate  
20 clocking or timing channel. Also, there may be constraints to the  
low frequency response of the designed transmission system. To  
remedy or mitigate these channel availability and frequency  
response constraints bi-phase level, self clocking PCM techniques  
are commonly employed. Unfortunately, such codes effectively  
25 reduce the available data and information bandwidth by half.  
These issues and associated remedies are discussed in "Digital  
Recording Methods", Magnetic Tape Recording Technical  
Fundamentals, Datatape Incorporated, 1976, pages 9599,

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 incorporated by reference herein for purposes of indicating the background of the invention and illustrating the mature state of the art. The rationale and utilization of bi-phase PCM technology is well known to those practicing the art.

10 Fig. 1 illustrates a typical prior art, single channel, digital PCM data transmission system.

Biphase PCM Waveform-21 is the digital PCM data input to Buffer Amplifier 22, representing a simple transmitter, comprising either digital or analog circuitry. A Fixed Transmission Line 23, featuring a single conductor per channel, each channel exhibiting both resistive and frequency dependent attenuation, conducts the output signal from Buffer Amplifier 22 to the input of simplified, typical Receiver 24, comprising Wide-band Amplifier 25 and Multipole Equalization Network 26. Wide-band Amplifier 25, employing either analog or digital circuitry, is used to

15 compensate for the attenuation of Waveform 21 upon transmission through the lossy Fixed Transmission Line 23. Output from Wide-Band Amplifier 25 thereupon goes to the input of Multipole Equalization Network 26. Although typically an active network Multipole Equalization Network 26 can also be a passive network.

20 Intended to reconstruct the degraded fidelity of the signal present at the input to Receiver 24 to a replication of Waveform 21 by compensating for the frequency dependent losses attendant to the Fixed Transmission Line 23, Network 26 tends to be complex

25

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 and difficult to implement. Although Network 26 may also include  
some techniques to correct the slope or rise time of the  
attenuated received signal, such techniques are often primitive  
and inadequate for reliable, high-quality digital PCM data  
transmission. This inadequacy typically is remedied by Bit  
10 Synchronizer 27, which processes the output from Multipole  
Equalization Network 26, correcting for slope and rise time  
degradation, and producing as an output, Reconstructed PCM  
Waveform 28, which is desired to be a replication of Bi-phase  
PCIV1 Waveform 21 of sufficient veracity and reliability to  
15 fulfill the intended purpose of the data transmission system.  
Unfortunately, as illustrated in Fig.1, Bit Synchronizer 27 is  
normally a separate, often necessary, add-on component to the  
typical receiver 24. Containing expensive, complex circuitry, this  
synchronizer component can cost thousands to tens of thousands of  
20 dollars; proper utilization often entails lengthy, difficult  
adjustments,

**SUMMARY OF THE INVENTION**

25 An object of the present invention is to provide a means for  
high fidelity reconstruction, i.e. low, acceptable bit error-  
rate, of an original pulse code modulation (PCM) serial stream  
binary data signal which has suffered degradation of fidelity,  
and consequent increase in bit-error-rate, during transmission on

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 a single channel from a transmitter to a receiver, connected to  
each other by a transmission line exhibiting both resistive and  
frequency dependent loss. This object is accomplished prior to  
transmission by amplitude encoded digital pre-emphasis of each  
10 bit of the original binary data signal to be transmitted in such  
manner as to mitigate or remedy the signal degrading frequency  
dependent losses concomitant with the signal transfer network  
characteristics of the fixed transmission line. Subsequent to  
this pre-emphasis process, the amplitude encoded signal is  
15 transmitted to the receiver connected to the other end of the  
fixed transmission line. Compared to a conventional transmitter,  
transmission line, and receiver system, the end result of  
amplitude encoded pre-emphasis is superior reconstructed fidelity  
and quality of the PCM waveform, i.e. lower bit-error-rate, at  
the output of the receiver for the same length of transmission  
20 line or, alternatively, a longer transmission line for the same  
bit error-rate.

A further object of the present invention is to reduce the  
complexity and cost of signal processing equipment at the  
receiver while maintaining a low, acceptable bit error-rate. As a  
25 consequence of employing the present invention, the excellent  
high fidelity reconstruction of the received, amplitude encoded  
signal obviates many requirements for complex, expensive signal  
processing equipment at or following the receiver, such as bit

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 synchronizers, filters, equalizers, and compensators.

**BRIEF DESCRIPTION OF THE DRAWINGS**

10 FIG. 1 is a simplified block diagram illustrating a typical prior art, single channel, digital PCM transmission system utilizing a bi-phase PCM waveform.

15 FIG. 2 is a simplified block diagram illustrating one embodiment of bi-phase PCM waveform pre-emphasis circuitry in accordance with the principles of the present invention.

20 FIG. 3 is a timing diagram illustrating various waveforms attendant to the present invention.

25 FIG. 4 is a schematic diagram of one embodiment of the PCM state detector and Multiplexer controller.

FIG. 5 is a schematic diagram of one embodiment of the PCM level adjustment.

FIG. 6 is a schematic diagram of one embodiment of the wide-band analog multiplexer and the buffer amplifier.

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 **DESCRIPTION OF THE PREFERRED EMBODIMENT**

R

10 The present invention amplitude encodes the serial stream  
binary PCM data signal containing digital PCM data which is to be  
transmitted to the receiver via a fixed transmission line. This  
encoding modifies the signal waveform by altering the individual  
amplitudes of each pulse-width interval prior to transmission.  
The present invention is particularly suited for performing  
digital pre-emphasis on the bi-phase level type binary serial PCM  
codes or the Delayed Modulation family of PCM codes. Individual  
15 amplitudes of these binary, pulse width intervals, commonly  
called Mark and Space, are manually or automatically mapped into  
series of discrete, constant amplitude steps, mitigating or  
remedying the undesired frequency dependent attenuation  
characteristics of the transmission line. The resultant encoded  
20 signal, which now varies in amplitude steps, is then transmitted  
through the transmission line. Upon transmission, frequency  
dependent characteristics of the transmission line degrade the  
transmitted data signal to an extent which is opposite to the  
mapped characteristics of the pre-emphasized signal prior to  
25 transmission. By compensating for the transmission line  
frequency dependent loss affecting digital PCM data, the present  
invention substantially reduces the increased bandwidth penalty  
imposed thereon and the received, amplitude encoded, signal is

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 more easily de-commutated and reconstructed with greater fidelity, i.e. reduced bit-error-rate, than a similar signal lacking this pre-emphasis. The resulting effect at the receiver is a constant amplitude signal, essentially the original, albeit attenuated, digital PCM data signal prior to amplitude encoding.

10 This received attenuated signal then requires only simple amplification to provide an amplitude level sufficient commutation (e.g., threshold detection) and subsequent reconstruction of the original digital PCM data. The present invention can be easily incorporated and operated with any  
15 transmission line network characteristic and length.

The present invention simplifies receiver electronics and permits increasing the length of cable linking the transmitter and the receiver without sacrificing increased degradation of the received PCM signal. Typically, PCM signals are transmitted  
20 through a cable with only single-pole pre-emphasis for improving transmission spectral characteristics. Multi-pole pre-emphasis can sometimes be utilized, however a change in the type of cable or cable length and its associated transmission spectral characteristics typically requires modification or redesign of  
25 the pre-emphasis applied to the signal. The same condition, and generally more severe and sophisticated, is the equalization or de-emphasis network at the receiver. Such networks, which can become quite complex, would require modification and redesign to



Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 restore the signal to a usable level if cable characteristics change or if the system is utilized on a different cable.

Example 1

10 An example of the utility of the present invention entails the employment of oceanographic data systems which transmit data through very long cables from a towed, submerged electronics package. Different ships utilize different types and lengths of cables and such cables have changing characteristics over time or under alternating operating conditions. The elegant simplicity and utility of this exemplary embodiment of the present invention is illustrated in a signal degradation problem that occurred when high speed serial digital PCM data were transmitted through a 7,500 meter coaxial cable connecting a submerged oceanographic data acquisition system to a recording subsystem located on board the towing ship.

15 Self-clocking PCM signals (synchronous or asynchronous) commonly utilize coding schemes like the family codes for Bi-phase and Delayed Modulation when transmitting serial data through single-ended cable. At the shipboard receiver, the degraded signal suffered from, (1) base-band attenuation (in this example, more than -50dB at 1 MHz); (2) additional attenuation of the high frequency band component for Bi-phase; and (3) considerable DC baseline shifting.

20

25

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 Adequately receiving such degraded signals required expensive  
Synchronizers (one such unit cost in excess of \$10,000) and De-  
commutators for extracting useable data from the signal stream.  
Also included at the receiver were amplifiers and equalization  
circuits to compensate for signal attenuation and degraded  
10 fidelity.

To minimize or eliminate the need for such complex, expensive  
equalization and signal is reconstruction at the receiver, the  
present invention was incorporated into the oceanographic data  
gathering system to improve signal restoration and consequently,  
15 decrease the bit-error-rate. Although the PCM signal therefrom  
became adversely modified by the cable due to cable  
characteristics, altering the DC signal baseline and the  
amplitudes of both high and low frequency band components, the  
present invention compensated for the cable response  
20 characteristics by applying a manually calibrated, multiple  
stepped, amplitude level adjustment to the PCM signal prior to  
transmission. As a result of the employment of the present  
invention, less varying DC baseline and nearly flat amplitude for  
all frequency and components was received. Laboratory testing  
25 demonstrated no data loss at transmission rates of 1-2 MHz through  
7,500 m of cable for more than 60 hours of continuous transmission.

In summary, the present invention eliminated the need for  
conventionally employed Bit-Synchronizer and De-commutator electronics  
and improved the bit-error-rate by several orders of magnitude.

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 To facilitate comprehending this particular and preferred  
embodiment of the present invention, Fig.2 illustrates, in block  
diagram form, a digital PCM data transmission system incorporating the  
present invention. Fig 2 shows the transmitter section connected to  
the Fixed Transmission Line 120, which, in turn, is connected to the  
10 receiver section 130. Bi-phase PCM waveform 60 represents the digital  
PCM data input to transmitted 50 and Reconstructed Digital PCM  
Waveform 60 represents the output of received 30, the desired  
replication of the digital PCM data input. Also included in Fig 2 are  
signals C, D, E, E', E", and C'. Fig. 3 portrays some of these various  
concomitant binary and analog waveforms associated with the present  
invention. The input Bi-phase PCM Waveform 60 is exemplified in  
Fig. 3 as Signal C, Bi-phase Level. As illustrated in Fig3, Signal C  
is the resultant product of combining Signal A, an NRZ (non-return to  
zero) signal containing data or information, and Signal B, a clock  
20 signal for synchronizing data flow. Techniques for combining Signal A  
and Signal B into Signal C are common and well known to those  
practicing the art. Signals A, B, C, and D are binary signals, whereas  
signal E is an analog signal appearing as a series of discrete,  
stepped amplitude levels. Signal D is a binary signal operating at  
25 twice the frequency of Signal B; and Signal E illustrates the pre-  
emphasized, multiple step level, analog bi-phase signal in accordance  
with the present invention. Signal E' is an amplified version of  
Signal E; Signal E" is an attenuated version of Signal E.

As illustrated in Fig. 3, and common to those practicing the art,  
30 the pulse width interval of the bi-phase level, Signal C, may be  
categorized in one of four possible states,

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 Long Mark, (designated: LM)- The longer duration of two possible binary signal levels designated as a Mark, the Mark level typically more positive than the alternative level designated as a Space

10 Long Space (designated- LS): The longer duration of two possible binary signal levels designated as a Space, the Space level typically less positive than the alternative level designated as a Mark

15 Short Mark (designated, SM): The shorter duration of two possible binary signal levels designated as a Mark

20 Short Space (designated: SS)- The shorter duration of two possible binary signal levels designated as a Space

Grouping together these four possible states as adjacent pairs of Space Mark or Mark Space states produces a new universe of 8 possible paired states:

25 Long Mark followed by Long Space, designated: LM LS  
Long Mark followed by Short Space, designated: LIVISS  
Short Mark followed by Long Space, designated- SIVILS  
Short Mark followed by Short Space, designated: SMSS  
Long Space followed by Long Mark, designated: LSLM  
Long Space followed by Short Mark, designated: LSSM  
30 Short Space followed by Long Mark, designated- SSLM  
Short Space followed by Short Mark, designated: SSSM

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5        These 8 possible conditions of level or states constitute the universe of mapped phase levels with digital preemphasis in accordance with the preferred embodiment of the present invention, illustrated in Fig.3 as Signal E.

10        In Fig. 2, transmitter 50 of the present invention comprises 2X Clock 70, PCM State Level Adjustment 80 (shown in more detail in Fig.5), PCM State Detector and Multiplexer Controller 90 (shown in more detail in Fig.4), Wide-bandwidth Analog Multiplexer 100 (shown in more detail in Fig.6), and Buffer Amplifier 10 (shown in more detail in Fig.6). As mentioned earlier, input to transmitter 50 is Biphasic PCM Waveform 60 (containing digital PCM data). At this point, biterror-rate is negligible and Signal C and Waveform 60 are essentially identical.

15        The PCM State Detector and Multiplexer Controller 90 performs the dual function of detecting the 8 possible MarkSpace and SpaceMark states of input Signal C and providing a corresponding multiplexer control signal to the Wide-bandwidth Analog Multiplexer 100. Responding to the multiplexer control signal, the Analog Multiplexer 100 is a wide-bandwidth multiplexer which selects a specific MarkSpace or SpaceMark mapping level. Adjustable DC voltages from the PCM State Level Adjustment 80 are selected by the Wide-bandwidth Analog Multiplexer 100 to map the detected, binary PCM Mark-Space or Space-Mark states of Signal C into new, variable step amplitude MarkSpace or SpaceMark levels to form the amplitude modulated PCM, Signal E. The mapped output, Signal E, from Multiplexer 100 is the input signal to Buffer Amplifier 10, which provides buffering, impedance matching, and amplitude control for the preemphasized signal to be subsequently

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 transmitted through a single channel of Fixed Transmission Line 120.  
In Figure 2, Signal E' is the amplified output signal from Buffer  
Amplifier 110; Signal E" is the attenuated output signal from the  
Fixed Transmission Line 120.

10 A preferred embodiment of PCM State Detector and Multiplexer  
Controller 120 is illustrated in Fig. 4 in circuit diagram schematic  
format. Signal C, i.e. the digital PCM data, Biphase PCM Waveform 60,  
is the input to Programmable Read-Only-Memory (PROM) U1, universal  
integrated circuit nomenclature 2764, or the like. This input is at  
address terminal A8 of PROM U1.

15 PROM U1 terminals, A10, A11, A12, CE, and OE are connected to the  
system ground bus. PROM U1 terminals PGM and VPP are connected to +5  
VDC source of power. Appropriate connection of the integrated  
circuitry of the present invention for purposes of system grounding  
20 and sources of power are common and well known to those skilled in the  
art and will not be discussed hereinafter. Upon detection of a  
particular Mad-Space and Space-Mark state, a corresponding state  
detector signal is generated as output from PROM U1, on detector  
output terminals, D0, D1, D2, D3, D4, D5, D6, and D7, connected,  
25 respectively, to controller input terminals, 1 D, 2D, 3D, 4D, 5D, 6D,  
7D, and 8D of Digital Latch U2, universal integrated circuit  
nomenclature 74HC574, or the like. These eight data lines represent  
the eight possible Mark-Space and Space-Mark states of the PCM signal,  
Signal C. PROM U1 and Digital Latch U2 are together configured as a  
30 serial shift register providing detection of the eight different Mark-  
Space and Space-Mark state conditions, listed hereinbefore, that can

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 exist for the Signal C.

10 Signal D from the 2X Clock 70 is applied to Digital Latch U2 to  
synchronize identification of each of the eight possible Mark-Space  
and Space-Mark conditions of state that can exist in Signal C. As  
shown in Fig.4, Signal D, a clock signal from 2X Clock 70, operating  
at twice the clock frequency of SignaB, is applied to the input of  
FirstInvertor U7A, universal integrated circuit nomenclature 74HC14,  
or the like. The output of the First Inverter U7A is applied both to  
the clocking terminal, CLK, of Digital Latch U2 and also to Second  
15 Inverter U713, universal integrated circuit nomenclature 74HC1 4, or  
the like. Output of Second Inverter U7B appears on Signal Line AA,  
reconstructed as Signal D (i.e. a double inversion of Signal D). From  
PROM U1, input address terminals, A0, A1, A2, A3, A4, A5, A6, and AT  
are connected respectively to controller output terminals, 1 Q, 2Q,  
20 3Q, 4Q, 5Q, 6Q, 7Q, and 8Q, of Digital Latch U2. These connections  
enable the state detector control signal generated by Digital Latch U2  
to feed back PROM U1 in order to detect the next condition of state of  
the serial data. This state detector control signal is presented as an  
address to PROW. The portion of the state detector control signal  
25 generated at controller output terminal 1Q appears on Signal Line BB;  
the portion of the state detector control signal generated at  
controller output terminal 2Q appears on Signal Line CC; and the  
portion of the state detector control signal generated at controller  
output terminal 3Q appears on Signal Line DD. These three output  
30 signals from 1 Q, 2Q, and 3Q of Digital Latch U2, appearing  
respectively on Signal Line BB, Signal Line CC, and Signal Line DD,

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 plus Signal D (the 2X clock signal) appearing on Signal Line AA,  
comprise the multiplexed control signal which is applied to the  
multiplexer input terminals of the Widebandwidth Analog Multiplexer  
100 (see Fig 2 and Fig. 6) to control selection of a specific DC  
adjusted mapping voltage representing the amplitude of the one of  
10 eight possible Mark-Space and Space-Mark states of Signal IC. In this  
particular embodiment, Multiplexer 100 is represented in Fig.6 as  
integrated circuit Multiplexer U3, universal integrated circuit  
nomenclature MAX440, or the like. The purpose of the output control  
signals utilized by Multiplexer U3 from outputs 1Q, 2Q, and 3Q of U2 is  
15 to select one of eight individually variable DC voltages representing  
an adjusted mapping amplitude of a specific Mark-Space or Space-Mark  
state condition.

These eight discrete DC voltage levels are determined by PCM State  
Level Adjustment 60, shown schematically for this embodiment as Fig5.  
20 Circuitry constituting Resistor R8, Resistor R4, Capacitor C1,  
Capacitor C2, Capacitor C3, and Capacitor C4 serves to provide voltage  
dividing from a source of DC power and also for suppression of  
transient noise. Such circuitry is well known by those practicing the  
art. Eight variable resistance devices, VR1, VR2, VR3, VR4, VR5, VR6,  
25 VR7, VR8, connected between a source of DC power and system ground,  
are manually adjusted to provide preemphasizer mapping voltages,  
respectively, to Mapping Voltage Line HH, Mapping Voltage Line GG,  
Mapping Voltage Line FF, Mapping Voltage Line EE, Mapping Voltage Line  
JJ, Mapping Voltage Line II, Mapping Voltage Line KK, and Mapping  
30 Voltage Line LL. These mapping voltage lines EE, FF, GG, HH, II, JJ,  
KK, LL serve as input, respectively, to IN0, IN1, IN2, IN3, IN4, IN5,



Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 IN6, and IN7, level adjustment input terminals of Multiplexer U3,  
shown in Fig.6. These DC mapping voltages are individually and  
manually adjusted to compensate for frequency dependent attenuation of  
Signal E', upon transmission through Fixed Transmission Line 20, as  
represented herein by Signal E". Such frequency dependent transmission  
10 line losses occur because a Short Mark or Short Space features a higher  
frequency component than a Long Mark or Long Space, and consequently,  
yielding differing amplitudes at the output of the transmission line.  
Thus, the amplitude mapping of the higher frequency signal component  
must be of higher magnitude than that of the lower frequency signal  
15 component to compensate for the greater attenuation suffered in the  
transmission line.

In the preferred embodiment, calibration of PCM State Level  
Adjustment 20 to subsequently provide pre-emphasis amplitude mapping  
of Signal C into the digital pre-emphasized signal, Signal E, is  
20 accomplished by observing, with an appropriate measuring instrument,  
such as an oscilloscope, the received signal at the output of Wide-  
Band Amplifier 140 (See Fig. 2) and manually and individually adjusting  
the eight variable resistance devices, V13 VR 2, VR 3, VR 4, VR 5, VR  
6, VR 7, and VR 8 of PCIVI State Level Adjustment 60 until the  
25 received signal features a constant amplitude. This procedure is not  
difficult and normally can be completed within three to five minutes  
by those of average skill in the art. Differences between Signal C and  
Signal E occur only in respect to individual amplitudes of the pulses,  
the width of such pulses does not differ; consequently, the original  
30 digital PCM data, represented as bi-phase PCM waveform 60, has not  
been altered.

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 In Fig. 6, the preemphasized mapped output signal of Multiplexer  
U3, represented as Signal E, is presented as an input signal to Buffer  
Amplified 10, Integrated Circuit Amplifier U4, universal integrated  
circuit nomenclature AD848, or the like. Additional circuitry  
concomitant with U4 includes, (1) a resistive network R1, R2, R3, and  
10 R 10, connected between the output of U3 and the input of U4,  
providing impedance matching and voltage dividing, and (2) a resistive  
network R7 and R9, connected between the output of U4 and input of  
Fixed Transmission Line 20, providing impedance matching. Design and  
implementation of both networks are well known in the art, and are not  
15 further discussed. Shown in Fig. 2, the output of Buffer Amplified  
10, an amplitude adjusted replication of Signal E, is Signal E', which  
is the input signal to Fixed Transmission Line 20. In like manner, the  
output signal from Fixed Transmission Line 20, an attenuated,  
frequency degraded version of Signal E', is Signal E", which is the  
20 input signal to Receiver 130.

As illustrated in Fig. 2, Signal E" is applied as an input signal  
to Receiver 130, comprising Wide-Band Amplifier 140 and Threshold  
Detector 150. The design and implementation of circuitry for Wide-Band  
25 Amplifier 140 and Threshold Detector 150 are well known to those  
practicing the art. Both circuits are common and implementation is  
relatively inexpensive. The output of Receiver 130 is Reconstructed  
PCM Waveform 160, represented as Signal C'. With proper calibration  
of PCM State Level Adjustment 80, mentioned hereinbefore, the veracity  
30 of Signal C', compared to Signal C, can be made sufficient to perform  
the intended purpose and fulfill requisite operational characteristics

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 of the aforementioned PCM data transmission system.

Example 2

10 The present invention described hereinbefore provides the basic or elementary level of implementation of transmitting pre-emphasized PCM codes through cable. In a second, more sophisticated (and expensive) embodiment of the present invention, calibration of PCM State Level Adjustment 80 can be automatic, vice manual, using a microcontroller and additional digital electronics to provide for remote calibration of the circuit through the cable. This more technically advanced version allows the calibration process to be performed dynamically and at a remote facility.

15 As applied to the example of the oceanographic data system, the digital reemphasizer was located within pressure vessels which were submerged to depths of up to 5,000 meters of water (about 7500 meters of cable). Since retrieval of the pressure vessels was both labor-intensive and time consuming, it was important to enable calibration of the reemphasizer while deeply submerged. A cost effective solution entailed the implementation of a microcontroller, firmware, and the addition of more electronic components to the basic circuit. It should be noted also that the basic description and application is applied for use in bi-phase level PCM code. The invention can use other codes which simply require a differently coded PROM (U1, Fig. 4) depending on the code used. The Delayed Modulation family of codes can be utilized by simply adding an additional PROM to detect the inherent additional states in the Delayed Modulation code. There are a host of other codes which this invention can be used for preemphasis. Because of the

Inventor: Ross  
Serial No.

**STATUTORY INVENTION REGISTRATION**  
Navy Case No. 76,736

5 simple nature of its use, the invention could be implemented into a Very Large Scale Integrated (VLSI) circuit which could provide for a single chip solution. Note also that this invention has commercial application in digital recording and in systems using data telemetry.

10 Although only a single exemplary embodiment of the invention has been described in detail above, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiment without materially departing from the novel teachings and advantages of this invention. Accordingly, all such modifications are intended to be included within the scope of this invention as defined in the following claims. In the claims, means-plus-functions clauses are intended to cover the structures described herein as performing the recited functions and not only structural equivalents but also equivalent structures.